

Specification Data Sheet | Model: 025TCC-EU(W)







TRANSCUBE CONTRACT 245 Ltr

UN (United Nations) IBC Intermediate Bulk Container, approved for transport of diesel fuel under the ADR Regulations. The Transcube Global is fully bunded steel in steel (to ensure environmental compliance with Pollution Prevention Guidelines (PPG2).

- 245 litre model can be transported full of diesel without the need for ADR Driver Training.
- Easily stacked to reduce storage space requirements.
- Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the TransCube Contract full of fuel.
- Secure lockable access hatch to house pumps (electric and hand), and feed and return connections for up to 1 generator.
- Size to stack inside shipping containers and across truck beds providing econmical transportation.
- Protective galvanised stack/lifting corner plates precenting damage to tank paintwork and decals..

SPECIFICATION			
Standard Tank Fittings: 1 x 2" Fill Point : 1 x 2" Vent Fill : Dipstick Tank Gauge : Pressure / Vacuum Vent : Breather Vent : 1 x 1" Pump & Auxiliary Feed : 1 x ½" Return : Pump Bracket			
Capacity (Brim Full) Litres:	245	Weight Unladen (kg):	220
Capacity (Brim Full) Gallons:	53	Weight Laden (kg):	440*
Dimensions Length (mm):	770	Bund Material (thickness):	S235 (2mm)
Dimensions Width (mm):	1150	Inner Tank Material (thickness):	S235 (2mm)
Dimensions Height (mm)	835	Design Approvals:	UN IBC Type 31A
Cabinet Dimensions:	To suit standard pumping equipment	Design Standards:	Bunded to COP Regulations (PPG2)
Notes			
* Specific gravity of diesel taken as 0.9 for this calculation			

Revision Date: 07/01/2016



